

V-AMMO

Vertical Deep and Shallow Mixed Metal Oxide Anode System (Imperial Units)

Custom configured V-AMMO (Vertical Anode utilizing Mixed Metal Oxide) suitable for all well anode applications. Fully customized, allowing designer flexibility for varying project conditions.



Overview

- Based on extensive experience manufacturing products and years of service utilizing specialty anodes for vertical anode applications.
- Designed and assembled using high quality materials manufactured in North America to the highest standards. Items are stocked for immediate assembly and quick shipping.
- Industry leading venting system ensures generated gases are vented efficiently providing optimum anode performance.
- Multi-component, chemical resistant layered anode-to-cable splices.

Fully Customized Ordering

Customized anode output:

- 150 mA/linear foot—40 year design life*
- 250 mA/linear foot—40 year design life*
- 250 mA/linear foot—20 year design life*
- 500 mA/linear foot—20 year design life*

* Based on well backfilled with carbon/coke for anode section.

Cable Selection

Can be ordered with either of the below cable types:

- HMWPE—High Molecular Weight Polyethylene—Standard Cathodic protection cable for shallow anodes.
- HALAR/HMWPE—Chemical resistant, recommended for deep well applications.

Note: To avoid drying the anode, limit the current density at the coke column-soil interface to 100 mA/sqft in clay and 150 mA/sqft in other soils.

Features & Benefits

- + North American assembled for quick shipping to job sites.
- + Reel-mounted assembling prevents damage and facilitates fast installation.
- + Premium HALAR/HMWPE chemical resistant cable option.
- + Suitable for any hole diameter larger than 6".
- + Built-in redundancy, including looped cable system and multiple cable to anode splices.
- + Light weight anode system reducing transportation costs for your project.
- + Multiple current outputs and life expectancy ensuring the anode system meets your project requirements.
- + Vent system is directly connected to anode ensuring immediate gas venting.

Technical Data

VENT PIPE		ORDERING
Filter Cloth	Particle blocking up to 0.011"	Included*
	Chemical resistant	Included*
Pipe Material	1" flexible polyethylene, c/w venting holes along the active anode area	Included*

* Unless specified otherwise the vent pipe is included as part of the system and can be ordered separately.

ANODE	CHECK ONE OF THE BELOW	
Output/Life	150 mA/linear foot—40 year design life	<input type="radio"/>
	250 mA/linear foot—40 year design life	<input type="radio"/>
	250 mA/linear foot—20 year design life	<input type="radio"/>
	500 mA/linear foot—20 year design life	<input type="radio"/>

CABLE TYPE	CHECK ONE OF THE BELOW	
Type	HALAR Ultimate chemical protection	<input type="radio"/>
	HMWPE Standard cathodic protection cable	<input type="radio"/>

CABLE SIZE	CHECK ONE OF THE BELOW	
Size	#4 AWG—Less than 5% Attenuation	<input type="radio"/>
	#6 AWG—Less Than 5% Attenuation	<input type="radio"/>
	#8 AWG—Less Than 5% Attenuation	<input type="radio"/>

LOWERING SYSTEM	CHECK ONE OF THE BELOW	
Rope	3/8" Polypropylene	Included
Weight	2" Carbon Steel (40lbs)	Included

ANODE WELL CABLE LENGTHS		
Active Anode Section	Length of active anode material	m
Non Active Anode Section	Length of cable between top of anode and well surface	m
Cable Tail	Length of cable extending outside from anode well	m

ATTENUATION		
Attenuation	Less than 5%	m

Recommended Uses

- Deep-well groundbeds 6" dia or more.
- Semi-deep well groundbeds 6" dia or more.
- Shallow-well groundbeds 6" or more.



To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact supplier to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for performance or injuries resulting from use. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.