

TRENTON®

Pre-Con®



Pre-Con® being poured into the casing through the casing vent.

Description:

Pre-Con® is a liquid casing water conditioner for pipeline casings. It consists of "wetting" and filming agents, vapor phase inhibitors, alkaline media additives and antibacterial conditioners.

End Use:

Pre-Con is poured into the casing prior to the installation of Trenton Fill-Coat® Casing Filler. The method of using these two materials together is a Trenton Corporation patented process.*

Pre-Con conditions the water accumulated in the casing so that any small amounts of water that may be entrapped after installation of Fill-Coat Casing Filler are inhibited and no corrosion should occur.

Application Procedures:

Prior to the filling operation, Pre-Con is poured directly into the casing through the casing vent and mixes with any water accumulated inside the casing. The casing can then be filled with Trenton Fill-Coat Casing Filler.

Packaging:

Pre-Con is packaged in five-gallon pails or is provided in bulk at the job site when Trenton crews install Fill-Coat Casing Filler.

Advantages:

Five gallons per 1,000 gallons of casing capacity.

Specifications:

Solubility in water	100%
Specific gravity	1.13
Color	Amber
Flash point	None

*Method covered under U.S. Patent #4,469,469 (License available through The Trenton Corporation, Ann Arbor, Michigan). 1/87



Corporate Office:

7700 Jackson Road
Ann Arbor, MI 48103 USA
(734) 424-3600
Fax: (734) 426-5882
trenton@trentoncorp.com

European Office:

8 rue d'Athènes
75009 Paris
France
+33 (0) 1 70 62 94 74
europe@trentoncorp.com

www.trentoncorp.com

Trenton Corporation is an ISO 9001 registered company